

DP-150

Printing Mechanism	Direct line thermal printer
Printing Speed	12 lines per second
Printable Logo	1 Black and White (384 x 336 dots)
Printable Barcode Types	EAN-13, EAN-8, UPC-A, UPC-E (printed by electronic scales)
Paper Width	58 mm
Paper Thickness	60 to 72 µm
Max Roll Diameter	50 mm
Paper Loading	Easy paper loading
Operator Display	96 x 16 Graphic LCD, Backlight
Customer Display	96 x 18 Graphic LCD (optional) Alphanumeric LCD, 2 lines of 16 symbols (optional)
Keyboard and Buttons	33 buttons
PLU database	Up to 100 000 PLUs
Inventory groups	9
Departments	9
Operators	30 (8 active)
TAX groups	8
Fiscal Memory	1850 reports
Payment types	Check, card, credit (programmable) Cash with alternative currency
Maximum number of sales	120 per receipt
Connectors	2 x RJ11 / RJ45 ports (digital scales, customer display, barcode reader, PC, Ethernet) Micro SD card slot (electronic journal)
Wired Communication	RS-232
GPRS (optional)	GSM/GPRS
Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 9 V, 1 A
Battery	Rechargeable Li-Ion battery 7.4 V, 2000 mAh
Dimension W x D x H	160 x 226 x 97 mm
Weight	526 g

