

Linea J

Microcontroller	Cortex-M3
Buttons	2 scan buttons 1 reset device button
Contactless Reader (optional)	ISO/IEC 14443 Type A MIFARE Mini, MIFARE Classic 1K, MIFARE Classic 4K, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Plus 2K, MIFARE Plus 4K, MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC
2D Barcode Reader	Newland EM3296 CMOS - 640 x 480 (optional) Newland EM3396 CMOS - 752 x 480 (optional) Intermec EA30 / ED40 CMOS - 752 x 480 (optional)
Connectors	USB Type-C port USB Micro connector (cradle)
Wired Communication	RS-232 USB (pass-through sync)
Device Compatibility	Galaxy J5 (2016)
Audio Features	Electromagnetic buzzer
Vibration Capabilities	14,000 rpm
Power Supply	DC 5 V through USB DC 5 V through contact pins
Battery	Rechargeable Li-Ion Battery 3.7 V, 2100 mAh Fuel Gauge
Dimension W x D x H	83 x 171 x 37 mm (with case) 77 x 164 x 34 mm
Weight	214 g (with case) 174 g
Operational Temperature	-10 °C to 40 °C / 5 to 90% RH
Storage Temperature	-20 °C to 50 °C / 5 to 90% RH
Box Contents	Linea J device Case Hand strap 90 cm USB Type-A to Type-C cable
Compatible Accessories	Charger (GT1) 5-unit charger (GT5) Dual charger Multi Battery Charger (MBC5) Case Hand strap

