

# WP-25

<b>Maximum number of items in database</b>	800 / 1200 / 1600 / 2400
<b>PLU name length</b>	Up to 42 characters
<b>Barcode types</b>	EAN-13, EAN-8, UPC, Barcode from a scale labels
<b>Tax type</b>	VAT, up to 7 rates – taxable, exempt or disabled
<b>Number of operators</b>	Up to 30
<b>Payments / maximum name length of payment</b>	5 programmable, up to 10 characters
<b>ECR operation modes</b>	<ul style="list-style-type: none"><li>- R / Registration</li><li>- S / Service mode</li><li>- X / Report</li><li>- T / Test</li><li>- Z / Report with clearing</li><li>- E / Electronic journal</li><li>- P / Programming</li><li>- H / Help mode</li><li>- Communication with PC</li><li>- M / Manufacturer mode</li></ul>
<b>Online communication with PC:</b>	<ul style="list-style-type: none"><li>- for programming, reading and report of the article data base</li><li>- for configuration of the cash register parameters</li></ul>
<b>Electronic journal</b>	SD card up to 32 GB
<b>Characters per line</b>	42
<b>Bluetooth modul</b>	Option
<b>Thermal printer</b>	Seiko LTP01-245-05
<b>Printer speed</b>	12 lines per second
<b>Graphics logo</b>	Supported size 384 x 96 dots (384 x 336 dots maximum)
<b>Barcode</b>	EAN8, EAN13, Code128, interleaved 2 of 5, QR code
<b>Paper width</b>	57 mm
<b>Paper thickness</b>	60 to 72 µm
<b>Max Roll Diameter</b>	30 mm
<b>Operator display</b>	Backlit graphic LCD
<b>Customer display</b>	Graphic LCD, 2 lines x 16 characters
<b>Keyboard</b>	33 keys
<b>Power supply</b>	DC 9 V / 5 A, DC 9 V / 3.5 A, input: 100 - 240 V, 50 - 60 Hz
<b>Battery</b>	Li-Ion 7.4 V 2000 mAh
<b>Operating temperature</b>	0 °C to 45 °C
<b>Dimension W x D x H</b>	162 x 235 x 64 mm
<b>Weight</b>	676 g
<b>Interface and additional devices</b>	Drawer output – 1 pcs., RS-232 (2 pcs.), Bluetooth, USB, LAN
<b>Communication (option)</b>	GSM / GPRS modem, LAN, or Wi-Fi module

